



Dušilci zvoka
Silencers

DUŠILCI ZVOKA / SILENCERS

SD



SDD



RSW



**

SDK



ST



Navoj Thread [A]	Tip Type	Hrupnost pri 6 bar Noise level at 6bar [v/in dB]	Tip Type	Hrupnost pri 6 bar Noise level at 6bar [v/in dB]	Tip Type	Hrupnost pri 6 bar Noise level at 6bar [v/in dB]	Tip Type	Tip Type
M5	SD-M5	/	/	/	/	/	/	/
G1/8	SD-18	81	SDD-18	73	RSW-18	72	SDK-18	ST-18
G1/4	SD-14	83	SDD-14	74	RSW-14	73	SDK-14	ST-14
G3/8	SD-38	87	SDD-38	85	RSW-38	84	SDK-38	ST-38
G1/2	SD-12	90	SDD-12	89	RSW-12	88	SDK-12	ST-12
G3/4	SD-34	92 pri / at 4 bar	SDD-34	90	/	/	SDK-34	ST-34
1"	SD-1	92 pri / at 4 bar	/	/	/	/	SDK-1	ST-1

** nastavljiv / adjustable

TEHNIČNI PODATKI / TECHNICAL FEATURES

Tip / Type	Material		Tlak / Pressure [bar]		Temperatura / Temperature [°C]	
	Ohišje / Body	Poroznost / Porosity [µm]	MAX.	MIN.	MAX.	
SD	Sinter bronza / Sinter bronze	50	10	-10	80	
SDD	Sinter bronza, medenina / Sinter bronze, brass	100	12	-10	80	
SDK	Polietilen / Polyethylene	75	10	-15	100	
RSW	Sinter bronza, medenina / Sinter bronze, brass	100	12	-10	80	
ST	POM	/	7 (G1/8 – G3/8) 10 (G1/2 – G1)	0	60	