

Špiralne cevi iz poliuretana

Polyurethane spiral hoses

PU 1190 – extraflex (ELASTOLAN) – z ravnim zaključkom / with straight terminals	16
PU 98 – longlife – z ravnim zaključkom / with straight terminals	16

ŠPIRALNA CEV Z RAVNIMI ZAKLJUČKI PU 1190 – extraflex (elastolan) SPIRAL HOSE WITH STRAIGHT TERMINALS PU 1190 – extraflex (elastolan)

– temperaturno območje uporabe od -40 °C do +60 °C
– can be used in a range of temp. from -40°C to +60°C

Tolerance / Tolerances:

± 0,07 debelina stene / on wall thickness
± 0,07 zunanji Ø do 12 mm / on outside Ø up to 12mm
± 0,1 zunanji Ø 14 mm / from outside Ø 14mm
± 0,5 % teže / on weight



Cev Tube	Dolžina Lenght [m]	Dimenzija v skrčenem stanju Out of work [mm]	Maks. delovna dolžina Max. Working lenght [m]	Št. špiral No. of Coils	Dolžina ravnih zaključkov Terminals lenght [mm]		Notranji / Zunanji Inside / Outside [mm]	Oznaka barve Color code
					levo / left	desno / right		
5,5x8x2,5C	2,5	190	2	22	120	500	25-41	A
5,5x8x5C	5	410	4	46	120	500	25-41	A
5,5x8x7,5C	7,5	660	6	78	120	500	25-41	A
5,5x8x10C	10	800	8	94	120	500	25-41	A
5,5x8x12,5C	12,5	1030	10	122	120	500	25-41	A
6,5x10x2,5C	2,5	2,5	2	13	120	500	40-60	A
6,5x10x5C	5	330	4	30	120	500	40-60	A
6,5x10x7,5C	7,5	500	6	45	120	500	40-60	A
6,5x10x10C	10	680	8	61	120	500	40-60	A
6,5x10x12,5C	12,5	800	10	76	120	500	40-60	A
8x12x2,5C	2,5	115	2	9	120	500	50-74	A
8x12x5C	5	305	3	24	120	500	50-74	A
8x12x7,5C	7,5	430	6	35	120	500	50-74	A
8x12x10C	10	600	8	48	120	500	50-74	A
8x12x12,5C	12,5	800	10	63	120	500	50-74	A
8x12x15C	15	930	12	77	120	120	50-74	A

Cev se lahko uporablja z zrakom, vodo in prašnimi barvami. Primerno za uporabo s vrtljivimi priključki na matico.
Hose can be used with air, water and powdered paint. Suitable to use with swivelling fittings.

ŠPIRALNA CEV Z RAVNIMI ZAKLJUČKI PU 98 – longlife SPIRAL HOSE WITH STRAIGHT TERMINALS PU 98 – longlife

– temperaturno območje uporabe od -40 °C do +60 °C
– can be used in a range of temp. from -40°C to +60°C

i V METALNIH BARVAH!
METALLIC COLORS!



Cev Tube	Dolžina Lenght [m]	Dimenzija v skrčenem stanju Out of work [mm]	Maks. delovna dolžina Max. Working lenght [m]	Št. špiral No. of Coils	Dolžina ravnih zaključkov Terminals lenght [mm]		Notranji / Zunanji Inside / Outside [mm]	Oznaka barve Color code
					levo / left	desno / right		
5,5x8x2,5C	2,5	190	2	22	120	500	25-41	AM-GM-RM-VM
5,5x8x5C	5	410	4	46	120	500	25-41	AM-GM-RM-VM
5,5x8x7,5C	7,5	660	6	78	120	500	25-41	AM-GM-RM-VM
5,5x8x10C	10	800	8	94	120	500	25-41	AM-GM-RM-VM
5,5x8x12,5C	12,5	1030	10	122	120	500	25-41	AM-GM-RM-VM
6,5x10x2,5C	2,5	140	2	13	120	500	40-60	AM-GM-RM-VM
6,5x10x5C	5	330	4	30	120	500	40-60	AM-GM-RM-VM
6,5x10x7,5C	7,5	500	6	45	120	500	40-60	AM-GM-RM-VM
6,5x10x10C	10	680	8	61	120	500	40-60	AM-GM-RM-VM
6,5x10x12,5C	12,5	800	10	76	120	500	40-60	AM-GM-RM-VM
8x12x2,5C	2,5	115	2	9	120	500	50-71	AM-GM-RM-VM
8x12x5C	5	305	3	24	120	500	50-71	AM-GM-RM-VM
8x12x7,5C	7,5	430	6	35	120	500	50-71	AM-GM-RM-VM
8x12x10C	10	600	8	48	120	500	50-71	AM-GM-RM-VM
8x12x12,5C	12,5	800	10	63	120	500	50-71	AM-GM-RM-VM
8x12x15C	15	930	12	77	120	500	50-71	AM-GM-RM-VM

Cev je primerna za uporabo s komprimiranim zrakom. Uporabna s PQS hitrimi priključki.
Hose is suitable to use with compressed air. Suitable to use with push-in automatic fittings PQS.